



Powered by Menasha Corporation

PRODUCT APPLICATION SHEET

GP4048-50

The medium-duty BulkPak® 4048 GP Series was designed for a wide variety of product sizes, shapes and weights.



These bulk containers allow more parts to be handled, stored and shipped...with fewer containers and in fewer trips. The advanced design results in a consistent tare weight that improves inventory and shipping efficiencies. Containers collapse when empty for reduced return transportation costs and warehouse space savings. During storage and shipping these bulk bins stack securely atop each other when full. Palletboxes offer the strength and rugged durability demanded in today's material handling and distribution systems. Custom protective dunnage is available for all ORBIS BulkPak containers. These plastic containers are fully recyclable at the end of their service life. (All dimensions and specifications are approximate. Performance characteristics are based on uniform static loads and may be affected distribution of load, handling methods, number and type of access doors and temperatures beyond the range of 0 to 120 degrees Fahrenheit.)

BENEFITS

- 40" x 48" x 50" footprint
- Structural-foam molded sidewalls and structural-channel molded base
- High-density polyethylene
- Container capacity: 1,500 lbs
- All-plastic construction eliminates risk of rust
- Self-standing sidewall for safe and efficient assembly and collapse
- Access Doors: 0, 1 or 2 doors on the 40" side (Door configurations vary by model)
- Base: All-plastic picture frame bottom or footcaps
- Deck: Solid or ventilated
- Sidewalls: Solid or ventilated
- Popular applications: Produce, caps/closures, plastic/rubber parts



Powered by Menasha Corporation

PRODUCT APPLICATION SHEET

	GP4048-50
Outside Top Dimensions Length	48.0"
Outside Top Dimensions Width	40.0"
Outside Top Dimensions Height	50.0"
Inside Top Dimensions Length	45.0"
Inside Top Dimensions Width	36.5"
Product Clearance	43.7"
Collapsed Height	17.7"
Container Capacity	1,500 lbs
Weight	177 lbs
Internal Volume	43.4 ft ³
Maximum Loaded Stack Static	4 high
Maximum Loaded Stack Dynamic	2 high
Return Ratio	2.89:1
Access Door Openings Height Short Side	19.0"
Access Door Openings Width Short Side	24.0"
Fork Openings Height Long Side	3.3"
Fork Openings Height Short Side	3.3"
Fork Openings Width Long Side	11.8"
Fork Openings Width Short Side	11.8"
40 Ft Container Quantities Without Covers Collapsed	105
40 Ft Container Quantities Without Covers Assembled	42
Truckload Quantities 53 Ft Without Covers Collapsed	180
Truckload Quantities 53 Ft Without Covers Assembled	60