



Powered by Menasha Corporation

PRODUCT APPLICATION SHEET

HDR5648-25 NV

Extended-length containers accommodate long and hard-to-fit components and parts.

The BulkPak® 5648 HDR Series accommodates long and hard-to-fit component parts. All containers are structural-foam molded in high-density polyethylene for durability and are available in side-loading Maximus styles. Unitized loads can be delivered directly to the assembly line for immediate part presentation, with no unwrapping or unbanding. Bulk containers collapse when empty for reduced return transportation costs and warehouse space savings. During storage and shipping these bulk bins stack securely atop each other. Palletboxes offer the strength and rugged durability demanded in today's material handling and distribution systems. Custom protective dunnage is available for all ORBIS BulkPak containers. These plastic containers are fully recyclable at the end of their service life. (All dimensions and specifications are approximate. Performance characteristics are based on uniform static loads and may be affected by distribution of load, handling methods, number and type of access doors and temperatures beyond the range of 0 to 120 degrees Fahrenheit.)

BENEFITS

- 56" x 48" x 25" footprint
- Fixed Walls
- Areas on all four sides for identification options
- Container capacity: 2,000 lbs
- Access doors: 0, 1 or 2 doors on 48" side and 2 standard doors on 56" side
- Deck: Solid with drain holes
- Sidewalls: Solid
- Base: All-plastic picture frame bottom with rounded legs for easy fork truck handling and reduced risk of "short forking"
- Popular applications: Automotive, appliance and transportation equipment



Powered by Menasha Corporation

PRODUCT APPLICATION SHEET

HDR5648-25 NV

Outside Top Dimensions Length	56.6"
Outside Top Dimensions Width	48.0"
Outside Top Dimensions Height	25.6"
Inside Top Dimensions Length	53.3"
Inside Top Dimensions Width	44.8"
Product Clearance	18.0"
Collapsed Height	13.6"
Container Capacity	2,000 lbs
Weight	171 lbs
Internal Volume	24.5 ft ³
Maximum Loaded Stack Static	6 high
Maximum Loaded Stack Dynamic	4 high
Return Ratio	2:1
Access Door Openings Height Long Side	12.2"
Access Door Openings Height Short Side	9.0"
Access Door Openings Width Long Side	44.3"
Access Door Openings Width Short Side	32.4"
Fork Openings Height Long Side	3.5"
Fork Openings Height Short Side	3.5"
Fork Openings Width Long Side	11.8"
Fork Openings Width Short Side	11.8"
40 Ft Container Quantities Without Covers Collapsed	72
40 Ft Container Quantities Without Covers Assembled	45
Truckload Quantities 53 Ft Without Covers Collapsed	176
Truckload Quantities 53 Ft Without Covers Assembled	88