



Powered by Menasha Corporation

## PRODUCT APPLICATION SHEET

# HDR6548-50

**Extended-length containers accommodate long and hard-to-fit components and parts.**



The BulkPak® 6548 HDR Series accommodates long and hard-to-fit component parts. All containers are structural-foam molded in high-density polyethylene for durability and are available in side-loading Maximus styles. Unitized loads can be delivered directly to the assembly line for immediate part presentation, with no unwrapping or unbanding. Bulk containers collapse when empty for reduced return transportation costs and warehouse space savings. During storage and shipping these bulk bins stack securely atop each other. Palletboxes offer the strength and rugged durability demanded in today's material handling and distribution systems. Custom protective dunnage is available for all ORBIS BulkPak containers. These plastic containers are fully recyclable at the end of their service life. (All dimensions and specifications are approximate. Performance characteristics are based on uniform static loads and may be affected by distribution of load, handling methods, number and type of access doors and temperatures beyond the range of 0 to 120 degrees Fahrenheit.)

### BENEFITS

- 65" x 48" x 50" footprint
- Areas on all four sides for identification options
- Extra wide access doors
- Container capacity: 2,000 lbs
- Access doors: 0, 1, 2, 3 or 4 doors
- Deck: Solid deck with drain holes
- Sidewalls: Solid
- Base: All-plastic picture frame bottom with rounded legs for easy fork truck handling and reduced risk of "short forking"
- Popular applications: Automotive, appliance and transportation equipment



Powered by Menasha Corporation

## PRODUCT APPLICATION SHEET

HDR6548-50

Outside Top Dimensions Length	64.5"
Outside Top Dimensions Width	48.0"
Outside Top Dimensions Height	50.0"
Inside Top Dimensions Length	61.3"
Inside Top Dimensions Width	44.8"
Product Clearance	42.9"
Collapsed Height	22.1"
Container Capacity	2,000 lbs
Weight	269 lbs
Internal Volume	68.0 ft <sup>3</sup>
Maximum Loaded Stack Static	4 high
Maximum Loaded Stack Dynamic	2 high
Return Ratio	2.3:1
Access Door Openings Height Long Side	24.4"
Access Door Openings Height Short Side	15.4"
Access Door Openings Width Long Side	50.3"
Access Door Openings Width Short Side	32.4"
Fork Openings Height Long Side	3.5"
Fork Openings Height Short Side	3.5"
Fork Openings Width Long Side	10.8"
Fork Openings Width Short Side	10.8"
40 Ft Container Quantities Without Covers Collapsed	36
40 Ft Container Quantities Without Covers Assembled	18
Truckload Quantities 53 Ft Without Covers Collapsed	72
Truckload Quantities 53 Ft Without Covers Assembled	36