



 Powered by Menasha Corporation

PRODUCT APPLICATION SHEET

HDR5648-25 NV

Extended-length containers accommodate long and hard-to-fit components and parts.

The BulkPak® 5648 HDR Series accommodates long and hard-to-fit component parts. All containers are structural-foam molded in high-density polyethylene for durability and are available in side-loading Maximus styles. Unitized loads can be delivered directly to the assembly line for immediate part presentation, with no unwrapping or unbanding. Bulk containers collapse when empty for reduced return transportation costs and warehouse space savings. During storage and shipping these bulk bins stack securely atop each other. Palletboxes offer the strength and rugged durability demanded in today's material handling and distribution systems. Custom protective dunnage is available for all ORBIS BulkPak containers. These plastic containers are fully recyclable at the end of their service life. (All dimensions and specifications are approximate. Performance characteristics are based on uniform static loads and may be affected by distribution of load, handling methods, number and type of access doors and temperatures beyond the range of 0 to 120 degrees Fahrenheit.)

BENEFITS

- 56" x 48" x 25" footprint
- Fixed Walls
- Areas on all four sides for identification options
- Container capacity: 2,000 lbs
- Access doors: 0, 1 or 2 doors on 48" side and 2 standard doors on 56" side
- Deck: Solid with drain holes
- Sidewalls: Solid
- Base: All-plastic picture frame bottom with rounded legs for easy fork truck handling and reduced risk of "short forking"
- Popular applications: Automotive, appliance and transportation equipment



Powered by Menasha Corporation

PRODUCT APPLICATION SHEET

HDR5648-25 NV

Outside Top Dimensions Length	1,438 mm
Outside Top Dimensions Width	1,219 mm
Outside Top Dimensions Height	650 mm
Inside Top Dimensions Length	1,354 mm
Inside Top Dimensions Width	1,138 mm
Product Clearance	457 mm
Collapsed Height	345 mm
Container Capacity	907 kg
Weight	77 kg
Internal Volume	0.69 m ³
Maximum Loaded Stack Static	6 high
Maximum Loaded Stack Dynamic	4 high
Return Ratio	2:1
Access Door Openings Height Long Side	310 mm
Access Door Openings Height Short Side	229 mm
Access Door Openings Width Long Side	1,125 mm
Access Door Openings Width Short Side	823 mm
Fork Openings Height Long Side	89 mm
Fork Openings Height Short Side	89 mm
Fork Openings Width Long Side	300 mm
Fork Openings Width Short Side	300 mm
40 Ft Container Quantities Without Covers Collapsed	72
40 Ft Container Quantities Without Covers Assembled	45
Truckload Quantities 53 Ft Without Covers Collapsed	176
Truckload Quantities 53 Ft Without Covers Assembled	88